

Point G2 – Large (BGS409 L)

Point G2 is a surface mounted, exterior-rated and compact sized architectural LED direct view dot lighting luminaire that is designed for façade and outdoor lighting applications.

The robust mechanical and unique optical covers make Point G2 ideal for building facades, bridges, theaters, amusement parks and recreational centers.

Available in white, monochromatic colors, RGB, RGBW and tunable white.

Three optical covers options and DMX control interface available to give architects and designers the freedom to explore a wide range of concepts and design with no limitations.

Key Features (BGS409 L)



- Low power LEDs to deliver smooth and soft direct view light
- Standard: RGBW, RGB, 3000K, 4000K and tW
- Optional 2700K, 5000K, 6500K, Monochromatic Colors
- Clear flat, opal and diamond spherical optical covers options
- Robust Design & IP66 rating for outdoor use
- Through wiring for power and DMX data via IP67 connectors
- Available in DMX512 control interface option

Ordering guide

ex: BGS409 L 10LED 40K 24V CFC DMX 9W


BGS409 L			24V			
Family	# of LEDs ⁽¹⁾	CCT / Color	Voltage	Cover Type	Control ⁽²⁾	Power
BGS409 L – Point G2	6LED 10LED 12LED	27K – 2700K 30K – 3000K 40K – 4000K 50K – 5000K RGB – RGB tW – Tunable White RGBWW – RGBW(3000K) RGBNW – RGBW(4000K) BL – Blue RD – Red GN – Green AM – Amber	24V – 24V DC	CFC – Clear Flat Cover OSC – Opal Spherical Cover DSC – Diamond Spherical Cover	– On/Off DMX – DMX	6W

(1) 6LED for RGB and RGBW, 10LED for White, 12LED for tW
 (2) RGB, RGBW and tW are only available in DMX control interface

Product Data

Product Family	Point G2 Large (BGS409 L)		
Dimensions (W x H x D)	114.4mm x 32mm x 104.4mm (CFC) 114.4mm x 64.3mm x 104.4mm (DSC) 114.4mm x 63.2mm x 104.4mm (OSC)		
Standard Optical Covers	Clear flat Opal spherical Diamond spherical		
Source	Low power LED		
Lumen Maintenance	50,000 hrs L70B50 at 35°C		
Housing	Die-cast aluminum		
Finishing	Electrostatically applied polyester powder coating		
Color	Dark Grey (RAL7012)		
Cover	Anti-aging and anti-UV PC Cover		
Gasket	Silicon		
Max Weight	0.31 kg		
Control Interfaces	On/Off DMX512		
Input Voltage	24V DC		
Maximum Current	6A		
IEC Classification	Class III		
Power Cable (On/Off)	2 pole flat cable L=30cm, 2x1.0mm ² with connectors		
Power/Signal Cable (DMX)	5 pole flat cable L=30cm, 2x1.0mm ² + 3x0.3mm ² with connectors		
Connectors	IP67 male/female connectors for through wiring		
Number of LEDs	6LED	10LED	12LED
Standard CCT/Color	RGB/RGBNW	4000K	tW
Max Power Consumption	9W		
Beam Angle/Cover	CFC OSC DSC		
Standard CRI	80		
White SDCM	4		
Colors Wavelengths	R: 620 to 625nm; G: 525 to 530nm; B: 470 to 475nm		
Temperature Range	-40°C to 50°C (Operating) -35°C to 50°C (Startup) -40°C to 70°C (Storage)		
Protection Rating	IP66, IK06		
Certification	CE, CB		
Warranty	3 Years		




Luminaire Dimensions:



CFC

DSC

OSC



CFC – Clear Flat Cover

Features:

The clear flat cover offers a higher luminance, sharper viewing angle and a more compact size.



OSC – Opal Spherical Cover

Features:

Use the spherical opal cover for a diffused and smooth lighting effect with a wider viewing angle



DSC – Diamond Spherical Cover

Features:

Use the diamond spherical cover for a more aesthetic look by day and unique light effect by night.



Order Information:

Description
BGS409 L 10LED 30K 24V CFC 9W
BGS409 L 10LED 40K 24V CFC 9W
BGS409 L 10LED 30K 24V OSC 9W
BGS409 L 10LED 40K 24V OSC 9W
BGS409 L 10LED 30K 24V DSC 9W
BGS409 L 10LED 40K 24V DSC 9W
BGS409 L 10LED 30K 24V CFC DMX 9W
BGS409 L 10LED 40K 24V CFC DMX 9W
BGS409 L 10LED 30K 24V OSC DMX 9W
BGS409 L 10LED 40K 24V OSC DMX 9W
BGS409 L 10LED 30K 24V DSC DMX 9W
BGS409 L 10LED 40K 24V DSC DMX 9W
BGS409 L 12LED tW 24V CFC DMX 9W
BGS409 L 12LED tW 24V OSC DMX 9W
BGS409 L 12LED tW 24V DSC DMX 9W
BGS409 L 6LED RGB 24V CFC DMX 9W
BGS409 L 6LED RGB 24V OSC DMX 9W
BGS409 L 6LED RGB 24V DSC DMX 9W
BGS409 L 6LED RGB40K 24V CFC DMX 9W
BGS409 L 6LED RGB40K 24V OSC DMX 9W
BGS409 L 6LED RGB40K 24V DSC DMX 9W
BGS409 L 6LED RGB30K 24V CFC DMX 9W
BGS409 L 6LED RGB30K 24V OSC DMX 9W
BGS409 L 6LED RGB30K 24V DSC DMX 9W


¹Other options are available upon request

Accessories:


Description
ZXP390 Lead 2P DC cable 2m (10 pcs)
ZXP390 Jump 2P DC cable 2m (10 pcs)
ZXP390 Lead 5P DC/DMX cable 2m (10 pcs)
ZXP390 Jump 5P DC/DMX cable 2m (10 pcs)
ZXP390 Y-connect kit 5P DC/DMX (10 pcs)
ZXP390 Jump 5P DMX connector (10 pcs)
ZXP390 endcap male connector (20 pcs)
ZXP390 endcap female connector (20 pcs)

¹ Different cables lengths are available upon request


² End caps must be used at the end of each run




Leader cable 2P DC 2m




Jumper cable 2P DC 2m




Leader cable 5P DC/DMX 2m




Jumper cable 5P DC/DMX 2m



Y-connector kit 5P DC/DMX



Endcap for male connectors



Endcap for female connectors

Rated System Lumen Output ($\pm 10\%$):

CCT/Color (All channels On)	CFC	OSC	DSC
	DMX	DMX	DMX
3000K			
4000K	555	360	675
tW	555	360	670
RGB	289	187	351
RGBNW	345	220	415
RGBWW			

